

CS14K6E-TFD

HFC, R-404A, 50 Hz, 3 - Phase, 380/420 V . [Also Available with Variable Frequency Drives](#)

Extended Medium Temp

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance			Mechanical	
Evaporator Temp. (°C)	-7	-23	Displacement (cm ³ /Rev):	47.19
Condensing Temp. (°C)	49	49	Displacement (m ³ /Hr):	
Return Gas Temp. (°C)	4	4	Overall Length (mm):	259.84
Liquid Temp. (°C)	49	49	Overall Width (mm):	245.11
Capacity (Watts)	3400	1304	Overall Height (mm):	341.38
Power (W):	1810	1130	Mounting Length (mm):	190.50
Current (Amps):	4.2	2.7	Mounting Width (mm):	190.50
EER(BTU/Wh):	10.87	6.80	Mounting Height (mm):	350.77
Mass Flow (lbs/hr):	36.29	13.48	Suction Size (mm),Type:	127.00 / 203.20 Stub
Sound Data @			Discharge Size (mm),Type:	25.40 / 50.80 Stub
Sound Power (dBA):	0 Avg	0 Max	Initial Oil Charge (ml):	1330.83
Vibration mils(peak-peak):	0.0 Avg	0.0 Max	Oil Recharge (ml):	1271.68
Record Date:	2014-10-02		Oil Type:	POE
			Net Weight (kg):	27.67
			Internal Free Volume (cm ³):	
			Horse Power:	
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical		Capacitors				
LRA High* (Amps):	28.0	Type	Part No	Low MFD	High MFD	Volts User Description
LRA Low*(Amps):		No data available in table				
LRA Half Winding (Amps):						
MCC (Amps):	6.6					
Max Operating Current (Amps):						
RLA, MCC/1.4(use for contactor selection)(Amps):	4.7					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	4.2					
RPM:						
Box IP :						
UL File No:						
UL File Date:	1984-12-28					

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-134a HFC	380/420	3	50	High Temp
R-134a HFC	380/460	3	60	High Temp
R-22 HCFC	380/460	3	60	Medium Temperature
R-404A HFC	380/460	3	60	Extended Medium Temp
R-407A HFC	380/460	3	60	Medium Temperature
R-448A HFO	380/460	3	60	Medium Temperature
R-449A HFO	380/460	3	60	Medium Temperature
R-507 HFC	380/420	3	50	Medium Temperature
R-507 HFC	380/420	3	50	Extended Medium Temp
R-507 HFC	380/460	3	60	Extended Medium Temp