

CS33K6E-TFD

HFC, R-404A, 50 Hz, 3 - Phase, 380/420 V . [Also Available with Variable Frequency Drives](#)

UL Medium Temp

Production Status:

Performance			Mechanical	
Evaporator Temp. (°C)	-7	-23	Displacement (cm ³ /Rev):	101.93
Condensing Temp. (°C)	49	49	Displacement (m ³ /Hr):	
Return Gas Temp. (°C)			Overall Length (mm):	259.84
Liquid Temp. (°C)			Overall Width (mm):	245.11
Capacity (Watts)	7547	2954	Overall Height (mm):	376.17
Power (W):	4130	2520	Mounting Length (mm):	190.50
Current (Amps):			Mounting Width (mm):	190.50
EER(BTU/Wh):	10.58	6.80	Mounting Height (mm):	385.83
Mass Flow (lbs/hr):			Suction Size (mm),Type:	177.80 / 203.20 Stub
Sound Data @			Discharge Size (mm),Type:	25.40 / 50.80 Stub
Sound Power (dBA):	Avg	Max	Initial Oil Charge (ml):	1330.83
Vibration mils(peak-peak):			Oil Recharge (ml):	1271.68
Record Date:			Oil Type:	POE
			Net Weight (kg):	35.83
			Internal Free Volume (cm ³):	
			Horse Power:	
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical		Capacitors				
		Type	Part No	Low MFD	High MFD	Volts User Description
LRA High* (Amps):	48	No data available in table				
LRA Low*(Amps):						
LRA Half Winding (Amps):						
MCC (Amps):	13.8					
Max Operating Current (Amps):						
RLA, MCC/1.4(use for contactor selection)(Amps):	9.9					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	8.8					
RPM:						
Box IP :						
UL File No:						
UL File Date:	1984-12-28					

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-134a HFC	460	3	60	High Temp
R-134a HFC	380/420	3	50	High Temp
R-404A HFC	460	3	60	Extended Medium Temp